

Instructions for COAST HL27 Headlamp

BATTERY INSTALLATION: The HL27 uses three AA alkaline batteries and are located in the rear of the headlamp. To access the battery compartment, pull the elastic head band slightly away from the battery pack. Remove the rubber battery pack cover by grasping the tab at the top of cover and pulling it away from the battery pack. Insert the batteries in the direction indicated inside the battery pack. Replace rubber battery pack cover, making sure that the cover is seated firmly over the rim of the battery pack. Never mix old and new batteries. Remove batteries before storing headlamp during non-usage.

LIGHT OPERATION: To turn on the light, fully depress the red power switch on top of the light. To turn off the light, depress the red switch on top of the light a second time. To adjust the brightness, turn the red Light Output Control Wheel located directly behind the power switch. Move to the right to increase the brightness and left to decrease the brightness.

FOCUS AND BEAM POSITION ADJUSTMENT: This headlamp is equipped with COAST's Pure Beam™ Focusing Optic System with Twist Focus which allows the user to choose between a broad flood beam and a focused Bulls-Eye Spot™ beam for long distance illumination. To adjust the beam into the broad, flood light mode, turn the Focus Ring around the lens of the light clockwise when wearing the headlamp. To adjust the beam into the Bulls-Eye Spot™ mode, turn the Focus Ring around the lens of the light counter clockwise when wearing the headlamp. The hinged beam adjustment allows you to tilt the beam of light down into position to illuminate objects directly in front of you or in your hands. To adjust the beam position, hold the housing of the light with one hand and tilt the head of the light where the red power button is located down and away from your head with the other hand.

HEAD STRAP ADJUSTMENT AND TOP STRAP REMOVAL: To adjust the HL27 to fit your head, slide the buckles on the side head strap and/or the top strap. It may be necessary to slide the head of the light and battery pack on the side head strap to center the light once the head band is adjusted to the proper size. The top strap can also be removed if desired. To remove the top strap, grasp one side of the strap holder where it attaches to the main housing and pull back, slightly flexing the strap holder, to release it from the main housing; then slide the rear part of the strap through the slot on top of the battery pack. Reverse the operation to re-install.

HARD HAT SAFETY HELMET CLIP USE: The HL27 includes helmet clips for use with **hard hat style** safety helmets. To use the helmet clips, loosen the side and top headbands to fit the helmet and attach the clips to the side strap of the headlamp, evenly spaced with two on each side. Note: One of the clips has a wider loop in order to fit over the area on the side headband where the Z cord is located. Put the headlamp on the safety helmet and attach the clips to the rim of the helmet. Some adjustment of the clip positions and head straps will be necessary for proper fit on safety helmets. Note: Clips are designed for use ONLY with HARD HAT style safety helmets. They are not acceptable for use on most sporting safety helmets.

MAINTENANCE: Wipe the external body with a damp cloth. Do not submerge.

WARRANTY POLICY: Coast Products guarantees this product to be free of defects in materials and workmanship for the life of the original purchaser. This guarantee does not cover normal wear and tear, nor damage resulting from misuse or neglect. If this product is defective, return it to us for a repair or replacement, along with a check for \$5.00 shipping and handling. Guarantee does not include batteries.

In USA:

COAST Warranty
8033 NE Holman Street
Portland, OR USA 97218

800.426.5858